



PREMIUM PRINTER SERIES - MINITOUCH

HP TIJ 2.5 technology

The HSAJET® MiniTouch is based on reliable HP TIJ 2.5 technology which delivers consistent, high-quality, fast printing, exceptional value, and ease of use.

Robust design

The elegant black aluminium casing underlines the robust design, making it perfect for being installed in production environments. A USB port is positioned on the side of the MiniTouch. A small cover protects it when not in use.

5.7" Touch Interface

Use the touch pen or simply a pointed finger to control the MiniTouch. Illustrative, easy-to-understand icons lead users through all phases of building a print job to make printing simple and fast.

Easy to integrate and use

The controller's small size enables it to fit wherever you want it. Using cables up to 15 m long, the controller can be mounted far from the actual point of printing. It can be operated straight from the touch interface or by using the remote controlling protocol, providing yet another integration tool.

Premium controller for Premium printheads

Our MiniTouch Premium version is made specifically for our Premium printheads, made from black powder-coated aluminium. The Premium printhead has a stainless-steel footplate, which ensures that the print head is completely free of static electricity. Furthermore, the footplate encloses the nozzle area to avoid air turbulence and provide optimum print quality for high-speed printing. Read more about the Premium printheads in separate flyer.

Choose from ½"-2" printheight

The HSAJET® Premium MiniTouch MTHP4 can control print height up to 2", either as single heads or in a combination of 1-, 2-, and 3-pen printhead



No time between prints

While the first print is being executed, you are able to setup the next layout for printing. Once the first layout has been printed, you can execute the prepared layout right away.

Advanced administrator options in software

Flexible user-level management guarantees that the correct data is printed. You are also able to grant user rights as desired and protect the data with a unique password. In addition, content may be filled using a prompt which, as an optional feature, must be validated by a different user to guarantee accuracy. The controller is preloaded with a number of language files to provide menus in different languages, as well as regional month and day names.

Print at breakthrough speeds of up to 300 m/min (984 ft/min) in 300 x 150 DPI

- GRAPHICS
- TEXT (ALPHANUMERICAL)
- COUNTERS
- PRINTLOG
- SHIFT CODES
- 1D & 2D CODES*
- DATE & TIME (REAL-TIME & ADJUSTED)
- WINDOWS FONTS

Technical Details

Technology

HP TIJ 2.5

Print height

Up to 50.8 mm / 2"

Printheads

1-, 2-, 3- or 4-pen Premium print-heads

Print distance

0.5-5.0 mm dependent on ink and speed, typically 0.5-2.0 mm (nozzle to print surface)

Voltage

100-240 VAC

Memory

2 GB internal

Screen

5.7" touch screen

Design software

MiniDraw (PC) or on controller

Software menu language

English (multiple languages)

Print functions, e.g.

Prompt
 User-defined print log

Print options

Variable DPI
 Left/Right, Upside-down
 Other side, Bidirectional
 Mirrored

Layout options

Object rotation in 90 interval
 Works with mm/inch/point/pixel

Remote controlling

Start/Stop
 Exchange job
 Change field content per print
 Change print preferences/parameters

Interface

Power supply (SUB D15 F)
 Printhead connections (4x RJ45)
 RS232 (serial)
 Ethernet (LAN) 100 Mbit
 USB 2.0
 Control connection (SUB D15)
 Encoder input 3-33 V (SUB D9)
 Input/Output 3-33 V (SUB D9)

Signals

Low ink signal
 Print signal
 Print message signal
 Signal-generator

Complies with

CE directives

Vertical resolution (DPI)	Horizontal resolution 75-2400 DPI (variable)* speed examples (m/min)			
	75 DPI	300 DPI	600 DPI	2400 DPI
600 DPI	304	76	38	10
300 DPI high speed	608	152	76	19
300 DPI (row A)	304	76	38	10
300 DPI (row B)	304	76	38	10

Housing

Black powder-coated aluminium

Weight

MTHP4: 0.87 kg / 1.92 lbs
 Power supply: 1.5 kg / 3.3 lbs

In the box

- MiniTouch Premium controller
- Power supply
- USB Key / Stylus pen
- CD w. software
- 25-pin M-M cable for power supply, 2.0 m

Accessories

- Sensor and encoder
- Bridges and brackets
- Mountings (Inocon 53 mm)
- Premium printheads (see other flyer)
- Standard cables and Hi Power cables for Premium printheads (see Premium Printheads flyer)

